



"basic" bi-directional ball valve

BIDIRECTIONAL BALL VALVE FEMALE - MALE SOLVENT SOCKET 1 ITEM 786



REFERENCE	DESCRIPTION	Net weight	Volumen (m ³)	contenido.peso bruto	Unidades lote
111D110	VÁLVULA DE BOLA BIDIRECCIONAL ENCOLAR MACHO - ENCOLAR HEMBRA PTFE 20	0.165	0.02244	6.39	40
111D111	VÁLVULA DE BOLA BIDIRECCIONAL ENCOLAR MACHO - ENCOLAR HEMBRA PTFE 25	0.210	0.02244	4.65	40
111D112	VÁLVULA DE BOLA BIDIRECCIONAL ENCOLAR MACHO - ENCOLAR HEMBRA PTFE 32	0.353	0.04117	7.79	30
111D113	VÁLVULA DE BOLA BIDIRECCIONAL ENCOLAR MACHO - ENCOLAR HEMBRA PTFE 40	0.606	0.04117	6.79	20
111D114	VÁLVULA DE BOLA BIDIRECCIONAL ENCOLAR MACHO - ENCOLAR HEMBRA PTFE 50	0.870	0.04880	10.08	15
111D115	VÁLVULA DE BOLA BIDIRECCIONAL ENCOLAR MACHO - ENCOLAR HEMBRA PTFE 63	1.444	0.04717	15.14	10



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62




tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es



ITEM 786 | BIDIRECTIONAL BALL VALVE FEMALE - MALE SOLVENT SOCKET

CÓDIGO	f	PESO (g)	DN	A	B	C	D	E	F	PN	MEDIDA
11D110	20	153	15	95	55	16	74	80	44	PN16	MÉTRICO
11D111	25	193	20	103	62	19	80	80	49	PN16	MÉTRICO
11D112	32	322	25	132	72	23	103	101	66	PN16	MÉTRICO
11D113	40	556	32	143	88	25	125	130	71	PN16	MÉTRICO
11D114	50	810	40	165	103	31	138	130	75	PN16	MÉTRICO
11D115	63	1263	50	194	120	38	177	170	89	PN16	MÉTRICO





Product Documents



Product Certificates

Company Certificates



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es