




'basic' bi-directional ball valve

Solvent socket outlet - electric actuator - PTFE

ITEM 653



| REFERENCE | DESCRIPTION | Net weight | Volumen (m ³) | Gross weight | Unidades lote |
|-----------|--|------------|---------------------------|--------------|---------------|
| 111D299 | BALL VALVE 220V ACTUATOR SOL.SOCK.OUTLET 20 | 0,9585 | 0,01553 | 1,2852 | 1 |
| 111D300 | BALL VALVE 220V ACTUATOR PLAIN OUTLET 25 | 2,1796 | 0,00891 | 2,367 | 1 |
| 111D301 | BALL VALVE 220V ACTUATOR PLAIN OUTLET 32 | 3,359 | 0,03648 | 3,593 | 1 |
| 111D302 | BALL VALVE 24-240V ACTUATOR PLAIN 40 | 2,5896 | 0,02243 | 3,368 | 1 |
| 111D303 | BALL VALVE 220V ACTUATOR PLAIN OUTLET 50 | 3,5333 | 0,02243 | 4,021 | 1 |
| 111D304 | BALL VALVE 24- 240V ACTUATOR PLAIN OUTLET 63 | 3,8223 | 0,03648 | 4,4123 | 1 |
| 111D305 | BALL VALVE 220V ACTUATOR PLAIN OUTLET 75 | 6,086 | 0,03648 | 6,68 | 1 |
| 111D306 | BALL VALVE 220V ACTUATOR PLAIN OUTLET 90 | 8,575 | 0,04460 | 9,269 | 1 |



ITEM 653 | Solvent socket outlet - electric actuator - PTFE

| CÓDIGO | f | Actuador | PESO (g) | DN | A | B | C | D | E | F | PN | MEDIDA |
|--------|----|----------|----------|----|-----|-----|----|-----|-----|-----|------|---------|
| 11D299 | 20 | H10 | 1077.6 | 15 | 86 | 55 | 16 | 227 | 177 | 44 | PN16 | MÉTRICO |
| 11D300 | 25 | H10 | 1119.48 | 20 | 94 | 62 | 19 | 232 | 177 | 49 | PN16 | MÉTRICO |
| 11D301 | 32 | H10 | 1258.8 | 25 | 122 | 72 | 23 | 243 | 177 | 66 | PN16 | MÉTRICO |
| 11D302 | 40 | H20 | 2118.7 | 32 | 131 | 88 | 25 | 265 | 177 | 71 | PN16 | MÉTRICO |
| 11D303 | 50 | H20 | 2375.84 | 40 | 150 | 103 | 31 | 282 | 177 | 75 | PN16 | MÉTRICO |
| 11D304 | 63 | H20 | 2839.8 | 50 | 177 | 120 | 38 | 390 | 177 | 89 | PN16 | MÉTRICO |
| 11D305 | 75 | H35 | 4550 | 65 | 216 | 150 | 45 | 401 | 177 | 119 | PN10 | MÉTRICO |
| 11D306 | 90 | H55 | 6630 | 80 | 257 | 181 | 51 | 450 | 177 | 140 | PN10 | MÉTRICO |



Product Documents



Product Certificates

Company Certificates

