



PVC check valves (with spring)

Solvent socket outlet - Viton seal

ITEM 266

REFERENCE	DESCRIPTION	Net weight	Volumen (m ³)	contenido.peso bruto	Unidades lote
1016501	V ANTI ENL VITON S/ENC 20	0.139	0.01553	5.88	40
1016502	V ANTI ENL VITON S/ENC 25	0.168	0.01553	6.89	40
1016503	V ANTI ENL VITON S/ENC 32	0.285	0.02244	9.04	30
1016504	V ANTI ENL VITON S/ENC 40	0.470	0.02244	9.94	20
1016505	V ANTI ENL VITON S/ENC 50	0.715	0.02244	9.07	12
1016506	V ANTI ENL VITON S/ENC 63	1.172	0.03129	12.29	10
1016507	V ANTI ENL VITON S/ENC 75	2.196	0.03129	9.34	4
1016508	V ANTI ENL VITON S/ENC 90	3.557	0.02244	7.65	2
1016559	V ANTI ENL VITON S/ENC 110	3.934	0.02244	8.40	2



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62




tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es




ITEM 266 | Solvent socket outlet - Viton seal

Código Vitón	A	Peso	B	C	D	PN	MEDIDA
16501	20	131	52	85	17	PN16	MÉTRICO
16502	25	174	59	95	19	PN16	MÉTRICO
16503	32	282	69	120	24	PN16	MÉTRICO
16504	40	471	85	133	26	PN16	MÉTRICO
16505	50	677	99	150	31	PN16	MÉTRICO
16506	63	1090	116	177	38	PN16	MÉTRICO
16507	75	2616	150	216	44	PN10	MÉTRICO
16508	90	4194	178	257	51	PN10	MÉTRICO
16559	110	4435	178	286	61	PN10	MÉTRICO





Product Documents



Product Certificates

Company Certificates



Pol. Ind. Plá Vallonga,
c/ Agua, 28
03006 ALICANTE (España)



+34 965 11 42 82



+34 965 11 48 62



tecnicocomercial@hidroten.es



Technical &
Commercial Service
+ 34 966 105 888



www.hidroten.es